

Leading Automotive Customer Service



► VelyenPremium

4EC1800


Electromechanical 2-post lift Asymmetric baseless 3.500 Kg Electronic Synchronization






General Features:

- Homologated and certified according to the new European Machinery Directive 2006/42/CE and Harmonized Standards EN 1493:2010.
- Asymmetric arms to permit an easier opening of doors. Equipped with telescopic arms and double screwed pad suitable to lift any type of vehicle.
- · SCS: New integrated informative system of Self-Diagnosis.
- · Electronic synchronization through inductive detectors.
- Low maintenance: Automatic and permanent lubrication of spindles and nuts.
- Maximum stability: High quality sliders to guarantee a perfect stability of the arm carriages.
- · High resistance spindles. Manual lowering of the vehicle in case of energy absent.





*	SIZE	mm
	A	3540
	В	2795
	Н	2000
	HC	2940
	HT	4040
	M	95
	R1	925
	R2	1540
	R3	620
	D.4	1040

Distance between columns	2795 mm
Load capacity	3500 Kg
Pick up height	95 mm
Lifting height	2010 mm
Lifting time	45 s
Arms length	Short: 620-1240 mm / Long: 925-1545 mm
Overall width	3540 mm
Overall height with	4040 mm
overhead conduit included	
Motor	3 phase 230/400 V - 50/60 Hz. 2 x 2,4 KW

► VelyenPremium

4EC1800

Electromechanical 2-post lift Asymmetric baseless 3.500 Kg Electronic Synchronization





CUSTOM DESIGN AND MANUFACTURE BY VELYEN



► SCS

Automatic and integrated Self-Control System, free maintenance



▶ DESIGN

Extensible arms with two and three telescopic sections to reduce or increase the minimum and maximum length of the arms the arms



DESIGN

Bigger distance between columns to permit an easier opening of the doors



► DESIGN

Double screwed pad extension designed to raise vehicles of lower pick-up height



DESIGN

Faster service time



► ELECTRIC / SAFETY

Equipped with ON/OFF switch to follows the most strict European Standards on Electric and Hidraulic Safety



▶ DESIGN

Baseless type



► SAFETY

Suit able to serve 100% of vehicles safely and in compliance with the new European Standards



► SAFETY

Toe-trapping protection through acoustic signal

► VelyenPremium

4EC1800

Electromechanical 2-post lift Asymmetric baseless 3.500 Kg Electronic Synchronization





CUSTOM DESIGN AND MANUFACTURE BY VELYEN



► OPTIONALS

Tools support



► OPTIONALS

Inspection lighting
Equipment 24V



► OPTIONALS

Special Pad 4 x 4



► OPTIONALS

Special ExpressPad with different height positions for greater ergonomics in daily work.



OPTIONALS

Wheel aligment support



OPTIONALS

Air & Energy supply



► OPTIONALS

Color customization







