

TECHNICAL DATA

CHAMP BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD

Part number	0033351
Model	Champ
Type	24V/5A

MAINS DATA (50/60HZ)

Output Voltage [V]	24
Output Current [A]	5
Number of phases	1
Rated Voltage range [V]	90-270VAC
Current at nominal voltage [A]	
Recommended supply fuse [A]	
Supply cable area	3 x 0,75mm ²
Supply cable length [m]	2,2M
Typical Supply Connector	
Output cable cross-section	1,5mm ² 1,5m

BATTERY CONNECTION

Output cable cross-section	1,5mm ² 1,5m
Output cable terminals (in unit)	
Output cable length [m]	
Typical Output connector	
Output Voltage [V]	24

ELECTRIC DATA

Standby Power Consumption [W]	
Power Consumption [W]	
Apparent Power Consumption [VA]	

Power Factor

Inrush current, do not tripp fuse of class [A]

Output Ripple <1%

Efficiency (at rated power and no cables) [%]

PROPERTIES

Ingress protection IP67

Ambient temperature range (at full output power) [deg C] -25C > +40C

Ambient max temp (with reduced output power) [deg C]

Cooling: 1=Fan, 2= Convection

Short Circuit Protection No

Wrong Polarity Protection

Cabinet Type

Certifications

HMI

HMI Language

Reporting No

Radio Communication No

Charging Curve Set

I/O-cards

CE No

UL No

CHARGING TIMES

6 Hours cap.ah/5h

8 Hours cap.ah/5h

10 Hours cap.ah/5h

12 Hours cap.ah/5h

CHARGER DIMENSIONS

Weight excl. cables [kg]

Weight incl. cables [kg] 1.1

Outer Dimensions Height [mm] 43

Outer Dimensions Width [mm]	150
-----------------------------	-----

Outer Dimensions Depth [mm]	80
-----------------------------	----

Min Spacing Required

SHIPPING DIMENSIONS

Shipping Weight [kg]	1.1
----------------------	-----

Box Height [mm]

Box Width [mm]

Box Depth [mm]

CHARGING

Charging Ionic

Charging Standard

Charging Gel

Charging Li-Ion

Charging AGM

Moisture Resistance	No
---------------------	----

Dusty Environment	No
-------------------	----

Outdoor use	No
-------------	----

Cold store	No
------------	----

Tropical	No
----------	----

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower E.D. Marketing AB.